

WHAT IS CLAIMED IS:

1. A method for accessing a subterranean zone from the surface, comprising:

- 5 forming an entry well bore from the surface;
 forming two or more slanted well bores from the entry well bore to the subterranean zone; and
 forming a substantially horizontal drainage pattern from the slanted well bores into the subterranean zone.

10

2. The method of Claim 1, wherein the two or more slanted well bores are radially spaced approximately equally around the vertical well bore.

- 15 3. The method of Claim 1, wherein three slanted well bores are formed.

4. The method of Claim 3, wherein the three slanted well bores are radially spaced around the
20 vertical well bore approximately 120 degrees apart.

5. The method of Claim 1, wherein the horizontal drainage patterns comprise lateral well bores.

- 25 6. The method of Claim 5, wherein the lateral well bores are configured to drain an area of the subterranean zone of at least 640 acres.

7. The method of Claim 1, further comprising
30 removing resources from the subterranean zone through the horizontal drainage patterns to the surface.

8. The method of Claim 1, further comprising forming an enlarged cavity in each of the slanted well bores proximate to the subterranean zone.

b6
b7C
b7D
b7E
b7F
b7G
b7H
b7I
b7J
b7K
b7L
b7M
b7N
b7O
b7P
b7Q
b7R
b7S
b7T
b7U
b7V
b7W
b7X
b7Y
b7Z
b8
b9
b10
b11
b12
b13
b14
b15
b16
b17
b18
b19
b20
b21
b22
b23
b24
b25
b26
b27
b28
b29
b30
b31
b32
b33
b34
b35
b36
b37
b38
b39
b40
b41
b42
b43
b44
b45
b46
b47
b48
b49
b50
b51
b52
b53
b54
b55
b56
b57
b58
b59
b60
b61
b62
b63
b64
b65
b66
b67
b68
b69
b70
b71
b72
b73
b74
b75
b76
b77
b78
b79
b80
b81
b82
b83
b84
b85
b86
b87
b88
b89
b90
b91
b92
b93
b94
b95
b96
b97
b98
b99
b100

9. A guide tube bundle, comprising:

two or more guide tubes;

wherein the two or more guide tubes comprise a first
5 aperture at a first end and a second aperture at a second
end;

wherein the guide tubes are configured
longitudinally adjacent to each other; and

wherein the longitudinal axis of the first apertures
10 are offset from the longitudinal axis of the second
apertures.

10. The guide tube bundle of Claim 9, wherein the
guide tubes are twisted around one another.

15

11. The guide tube bundle of Claim 10, wherein the
twist comprises approximately 10 degrees.

20

12. The guide tube bundle of Claim 9, wherein:
the guide tubes are configured longitudinally
adjacent to each other at the first ends; and
the guide tubes are separated at the second ends.

13. A method for orienting well bores, comprising:
forming an entry well bore from the surface;
inserting a guide tube bundle into the entry well
5 bore, the guide tube bundle comprising:
two or more guide tubes, wherein:
the two or more guide tubes comprise a first
aperture at a first end and a second aperture at a second
end;
10 the guide tubes are configured longitudinally
adjacent to each other; and
the longitudinal axis of the first apertures
are offset from the longitudinal axis of the second
apertures; and
15 forming two or more slanted well bores from the
entry well bore, through the guide tube bundle.
14. The method of Claim 13, wherein:
the first aperture of each guide tube is oriented
20 horizontally; and
the second aperture of each guide tube is oriented
at an angle relative to the first aperture.
15. The method of Claim 13, wherein the guide tubes
25 are twisted around one another.
16. The method of Claim 15, wherein the twist
comprises approximately 10 degrees.

17. The method of Claim 13, wherein:
the guide tubes are configured longitudinally
adjacent to each other at the first ends; and
5 the guide tubes are separated at the second ends.

18. A system for accessing a subterranean zone from the surface, comprising:

- an entry well bore extending from the surface;
- two or more slanted well bores extending from the
- 5 entry well bore to the subterranean zone; and
- a substantially horizontal drainage pattern extending from the slanted well bores into the subterranean zone.

10 19. The system of Claim 18, wherein the two or more slanted well bores are radially spaced approximately equally around the vertical well bore.

15 20. The system of Claim 18, further comprising three slanted well bores.

21. The system of Claim 20, wherein the three slanted well bores are radially spaced around the vertical well bore approximately 120 degrees apart.

20 22. The system of Claim 18, wherein the horizontal drainage patterns comprise lateral well bores.

23. The system of Claim 22, wherein the lateral

25 well bores are configured to drain an area of the subterranean zone of at least 640 acres.

24. The system of Claim 18, further comprising an enlarged cavity in each of the slanted well bores

30 proximate to the subterranean zone.